

NECESAR ROBINETI, FITINGURI, FERONERIE

Nr. crt.	Denumire produs	UM	Cant.	Cant.
LOT 1				
1	Robinet inchidere cu ventil DN 25, PN16, corp cu flanse, material corp/capac: fonta cenusie, etansare: inox/inox, actionare manuala	buc	2	2
2	Robinet inchidere cu ventil DN 50, PN16, corp cu flanse, material corp/capac: fonta cenusie, etansare: inox/inox, actionare manuala	buc	2	2
3	Robinet inchidere cu ventil DN 125, PN16, corp cu flanse, material corp/capac: fonta cenusie, etansare: inox/inox, actionare manuala	buc	1	1
4	Robinet inchidere cu sertar cauciucat DN 50, PN 16, corp oval , corp cu flanse, material corp/capac: fonta ductila, sertar EPDM, actionare manuala	buc	2	2
5	Robinet inchidere cu sertar cauciucat DN 80, PN 16, corp oval , corp cu flanse, material corp/capac: fonta ductila, sertar EPDM, actionare manuala	buc	2	2
6	Robinet inchidere cu sertar cauciucat DN 125, PN 16, corp oval , corp cu flanse, material corp/capac: fonta ductila, sertar EPDM, actionare manuala	buc	1	1
7	Flansa plata otel DN 25, PN 16	buc	2	2
8	Flansa plata otel DN 50, PN 16	buc	4	4
9	Flansa plata otel DN 80, PN 16	buc	2	2
10	Flansa plata otel DN 125, PN 16	buc	2	2
11	Garnitura clingherit DN 25	buc	6	6
12	Garnitura clingherit DN 50	buc	6	6
13	Garnitura clingherit DN 80	buc	6	6
14	Garnitura clingherit DN 125	buc	8	8

LOT 2				
1	<p>Robinet de inchidere cu ventil DN 15, PN 160, corp din material inox complet, echivalent SS316Ti (W1.4571), sudura cap la cap (butt weld), corp cu capete pentru sudura, actionare manuala si roata de manevra. Caracteristici: - Fluid apa demineralizata; - Presiune 125 bar; - Temperatura de lucru: 310/320 grade Celsius.</p>	buc	100	100
TOTAL LOT 2				